



Personas 74 Interior

- Easy to use, easy to see
- Ergonomic design for ease of use
- New revenue opportunities
- Color customize to deliver brand recognition

NCR's intelligent and highly functional Self-Service Touchpoints™ can turn your existing infrastructure into a strategic weapon. Our solutions help you to build better customer relationships, generate new revenue streams and migrate more transactions to a cost-efficient channel. Our Web enabled Self-Service Touchpoints™ are the physical presence required for e-commerce fulfilment and mobile lifestyles. Making the virtual tangible.

The **Personas 74** offers key opportunities for expanding the self-service channel and making the most of what, for many people, is the main point of contact with their bank. It is an interior ATM which, in addition to dispensing cash, provides services such as account transactions and inquiries. As well as offering banks a convenient method of performing activities traditionally handled by the teller, there is a clear opportunity for

generating additional revenue by dispensing non-cash items such as stamps, tickets and coupons. The high quality graphic printer also allows for the easy inclusion of logos and other graphical images and can be used, for example, to print discount vouchers.

The design is the result of exhaustive research, development, and testing – so customers will find it convenient and easy to use with a large, highly visible color display. Importantly, since the **Personas 74** may be your customers' main point of contact, branding is also available. NCR offers a complete color customization service to match and reinforce your brand identity whatever the location.

Its compact size means that it can be installed in a wide range of interior locations, with front or rear access and a vestibule variant ensuring that the customer can get cash – and more – in all environments.

To ensure your investment is protected, the modules in the **Personas 74** will be fully upgradeable.

The **Personas 74** is part of a comprehensive portfolio of self-service



solutions from NCR, focused on quality and reliability, on delivering an enhanced range of solutions for our customers, and an improved range of services for the consumer.

The **Personas 74** from NCR. Cash and more.

Specifications

<p>Multimedia Interface</p> <p>15" (381mm) VGA color screen with privacy filter option</p> <p>8 tactile function display keys or touch screen interface</p> <p>Ruggedized tactile 16 key keyboard</p> <p>Swipe, dip or motorized card reader with smart card option</p> <p>EMV 3.1.1 compliant smart card reader</p> <p>Private audio or digitized audio system</p>	<p>Technical Specification</p> <p>PRODUCT DIMENSIONS</p> <p>Height 55.87" (1419mm)</p> <p>Width 24.8" (630mm)</p> <p>Depth 36.97" (939mm)</p> <p>Weight 1407lb (638kg) – UL</p> <p>DISPENSERS</p> <p>1,2,3 or 4 denomination options with bunch, retract and purge capability</p> <p>NCR universal polycarbonate multimedia cassette with 11.6" (295mm) capacity</p>	<p>CAN/CSA – B651 Barrier Free Design</p> <p>Australian Standard – AS 3769</p> <p>ELECTROMAGNETIC COMPATIBILITY</p> <p>Emission</p> <p>FCC Category A (USA)</p> <p>EN 55022 (1987) Class A</p> <p>Immunity</p> <p>EN 50082-1 Part 1 (1992)</p> <p>Generic Immunity Standard</p> <p>Radiated Immunity – IEC 1000-4-3</p> <p>Electrostatic Discharge – IEC 1000-4-2</p> <p>Fast Transients – IEC 1000-4-4</p> <p>Surge Immunity – IEC 1000-4-5</p>
<p>Printer Specification</p> <p>RECEIPT PRINTER</p> <p>40 column graphics thermal printer</p> <p>Capacity up to 5000 transactions</p> <p>4.4" (112mm) receipts</p> <p>Form length 4.4-7.5" (112-190mm)</p> <p>Optional sideways feature allows 80 column x 20 row mini statement</p> <p>JOURNAL PRINTER</p> <p>40 column graphics thermal or dot matrix printer</p> <p>Capacity up to 5000 @ 5 line journal entries</p>	<p>SECURITY</p> <p>Physical</p> <p>UL 291 Level 1</p> <p>High level – meets RAL 626/3</p> <p>UK – Special – (TL 30 Derivative)</p> <p>CEN Grade A3</p> <p>INFORMATION</p> <p>HI-BAPE (DES)</p> <p>EKC (DES, RSA limited to initial key exchange), enhanced physical protection</p> <p>ELECTRONIC PLATFORM</p> <p>Pentium or Pentium II processor</p> <p>ACCESSIBILITY</p> <p>Subject to compliance with NCR site preparation and installation guidelines, the NCR PXX complies with ADAAG 4.34.2, 4.34.3, and 4.34.4. NCR cannot certify or warrant compliance with ADAAG 4.34.5.</p>	<p>EMC DIRECTIVES</p> <p>89/336/EEC EMC Directive</p> <p>92/31/EEC Amending EMC Directive</p> <p>73/23/EEC Low Voltage Directive</p> <p>ENVIRONMENTAL</p> <p>Operating temperature: 50°F (10°C) to 104°F (40°C)</p> <p>Relative humidity: 20% to 80%</p> <p>ACOUSTICS</p> <p>Sound power: max 65dba idle, 68dba operating</p>



Transforming Transactions into Relationships



The future of self-service software solutions

NCR Financial Solutions Group Ltd
206 Marylebone Road London NW1 6LY

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed in all parts of the world. Consult your NCR representative for the latest information.

www.ncr.com

©2000 NCR Corporation

SP 6061