



Personas 85 Full-function exterior

- Easy to use, easy to see
- Exterior use for non-stop access
- Expand your service offering
- New revenue opportunities
- Color customize to deliver brand recognition

NCR's intelligent and highly functional Self-Service Touchpoints™ can turn your existing infrastructure into a strategic weapon. Our solutions help you to build better customer relationships, generate new revenue streams and migrate more transactions to a cost-efficient channel. Our Web enabled Self-Service Touchpoints™ are the physical presence required for e-commerce fulfilment and mobile lifestyles. Making the virtual tangible.

The **Personas 85** offers key opportunities for expanding the self-service channel and making the most of what, for many people, is the main point of contact with their bank. It is a full-function exterior ATM, providing a range of services such as dispensing cash, cashing checks, paying bills, account inquiries, passbook and document printing.

As well as offering banks a convenient method of performing activities



traditionally handled by the teller, there is a clear opportunity for generating additional revenue by dispensing non-cash items such as stamps, tickets and coupons. The high quality graphic printers also allow for the easy inclusion of logos and other graphical images. The receipt printer can be used, for example, to print discount vouchers and the statement printer for loan agreements.

The design is the result of exhaustive research, development, and testing – so customers will find it convenient and easy to use with a large, highly visible color display. Importantly, since the **Personas 85** may be your customers' main point of contact, branding is also

available. NCR offers a complete color customization service to match and reinforce your brand identity whatever the location.

As well as being suitable for new installations, the **Personas 85** has been designed to provide an easy upgrade path from existing NCR ATMs.

The **Personas 85** is part of a comprehensive portfolio of self-service solutions from NCR, focused on quality and reliability, on delivering an enhanced range of solutions for our customers, and an improved range of services for the consumer.

The **Personas 85** from NCR. Cash and more.

Specifications

<p>Multimedia Interface</p> <p>10" (254mm) VGA color screen with privacy filter option and sunlight visibility option</p> <p>8 tactile function display keys</p> <p>Ruggedized tactile 16 key keyboard</p> <p>Motorized card reader with smart card option</p> <p>EMV 3.1.1 compliant smart card reader</p> <p>Private audio or digitized audio system</p>	<p>24 pin dot matrix, magnetic read write, last line and page detect</p> <p>Statement/passbook feature for dual function</p> <p>9 pin dot matrix, magnetic read write, last line and page detect</p>	<p>ACCESSIBILITY</p> <p>Subject to compliance with NCR site preparation and installation guidelines, the NCR PXX complies with ADAAG 4.34.2, 4.34.3, and 4.34.4. NCR cannot certify or warrant compliance with ADAAG 4.34.5.</p> <p>CAN/CSA – B651 Barrier Free Design</p> <p>Australian Standard – AS 3769</p> <p>ELECTROMAGNETIC COMPATIBILITY</p> <p>Emission</p> <p>FCC Category A (USA)</p> <p>FTZ VDE 871/875 (Germany) Class A</p> <p>EN 55022 (1987) Class A</p> <p>CISPR 22 Class A</p> <p>Immunity</p> <p>EN 50082-1 Part 1 (1992)</p> <p>Generic Immunity Standard</p> <p>Radiated Immunity – IEC 801-3</p> <p>Electrostatic Discharge – IEC 801-2</p> <p>Fast Transients – IEC 801-4</p> <p>EMC Directives</p> <p>89/336/EEC EMC Directive</p> <p>92/31/EEC Amending EMC Directive</p> <p>73/23/EEC Low Voltage Directive</p> <p>ENVIRONMENTAL</p> <p>Operating temperature: -30°F (-35°C) to 122°F (50°C) (external)</p> <p>Relative humidity: 10% to 100%</p> <p>ACOUSTICS</p> <p>Sound power: max 55dbA idle, 60dbA operating</p> <p>Sound pressure: 55dbA operating</p>
<p>Printer Specification</p>	<p>Technical Specification</p> <p>PRODUCT DIMENSIONS</p> <p>Fascia height 23" (584mm)</p> <p>Fascia width 28.11" (714mm)</p> <p>Depth 45.3" (1151mm)</p> <p>Weight 1557lb (706kg) - UL</p> <p>DISPENSERS</p> <p>1,2,3 or 4 denomination options with bunch, retract and purge capability</p> <p>NCR universal polycarbonate multimedia cassette with 11.6" (295mm) capacity</p> <p>Optional 4 denomination coin dispenser</p> <p>SECURITY</p> <p>Physical</p> <p>UL 291 Level 1</p> <p>High level – meets RAL 626/3</p> <p>UK Special – (TL 30)</p> <p>CEN Grade A3</p> <p>INFORMATION</p> <p>HI-BAPE (DES)</p> <p>EKC (DES, RSA limited to initial key exchange), enhanced physical protection</p> <p>ELECTRONIC PLATFORM</p> <p>Pentium or Pentium II processor</p>	
<p>RECEIPT PRINTER</p> <p>40 column graphics printer</p> <p>Capacity up to 5000 transactions 4.4" (112mm) receipts</p> <p>Form length 4.4-7.5" (112-190mm)</p> <p>Optional sideways feature allows 80 column x 20 row mini statement</p> <p>JOURNAL PRINTER</p> <p>40 column graphics thermal or dot matrix printer</p> <p>Capacity up to 5000 @ 5 line journal entries</p> <p>STATEMENT PRINTER</p> <p>80 column letter quality thermal printer</p> <p>Capacity up to 800 sheets 12" (305mm)</p> <p>Form length 4-12" (102-305mm)</p> <p>Document capture</p> <p>Full graphics option</p> <p>PASSBOOK PRINTERS</p> <p>Page-turning passbook printer for horizontally stitched books</p> <p>4" (101.6mm) bunching capability</p> <p>Document capture</p>		



Transforming Transactions into Relationships



The future of self-service software solutions

NCR Financial Solutions Group Ltd
206 Marylebone Road London NW1 6LY

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed in all parts of the world. Consult your NCR representative for the latest information.

www.ncr.com

©2000 NCR Corporation

SP 6064