

Full-Function, Through-The-Wall ATM

MX7600XLT

Designed to provide unprecedented reliability, the **MX7600XLT** is unparalleled in the market. This full-function through-the-wall ATM can easily be upgraded from a cash dispenser to deposit automation and supports large volume transactions. The **MX7600XLT's** highest uptime and minimum maintenance has helped make Hyosung the fastest growing ATM company in the US.

KEY FEATURES

HIGH AVAILABILITY

Innovative design and the use of Hyosung manufactured core technologies allows for fast, easy replenishment and reduced down time.

The **MX7600XLT** is designed to provide reliability that is unequaled in the market, with minimum maintenance and maximum uptime.

FLEXIBILITY

The MX7600 series can also be easily upgraded from a cash dispenser to deposit automation should an institution decide to implement the technology later.

CAPACITY

High capacity, cash dispense capability and the ability to support large volume transactions.

SECURITY OPTIONS

Hyosung ATMs defend against physical and logical attacks with a multi-level locked down operating system, anti-skimming, white-listing, and encryption.





Full-Function, Through-The-Wall ATM

MX7600XLT

SPECIFICATIONS

DIMENSIONS

- Height: 58.1"
- Width: 28.4"
- Depth: 40.6"
- Weight: 1,978 lbs.

ENVIRONMENTAL

- Temperature: 32°F 104°F (0°C ~ 40°C)
- Humidity 25% 85%

SOFTWARE

- Microsoft Windows® 7
- Windows 10 ready

CUSTOMER INTERFACE

- 15" TFT LCD
- Input Method Touch screen
- Privacy Filter 15" filter
- PIN Pad PCI compliant
- ADA audio guidance earphone jack
- Card Reader DIP reader, EMV compliant

MEDIA TECHNOLOGY

• Dispense

- Configurable denominations up to 4 cassettes
- 3,000 notes per cassette
- Bundle present, bundle retract

Cash & Check InModule (CCIM)

- Maximum capacity 50 checks/cash per bundle per transaction
- Check cassette capacity 2000 note (CCIM)
- Cash cassette capacity 2000 note (CCIM)
- Reject and retract capability

SECURITY

- Safe: UL291 Level 1
- Alarm Seismic + Heat
- Locking Device Electronic, mechanical combination lock, Kaba Mas Cencon lock (optional)
- Security camera

SERVICING

- Rear access
- State of health indicators across

*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

Features and benefits are for U.S. configuration only. If located outside of the U.S., please contact sales.

PRINTER

• 3.1" graphical thermal receipt printer

ADDITIONAL INFORMATION

- Communication TCP/IP
- Backup battery reserves the last transaction & safe shutdown