

# **MX7800I**

Hyosung is revolutionizing the ATM self-service industry. The MX7800I enables customers to choose how they want to interact with your financial institution by offering a robust set of transactions through Hyosung's industry-leading core integration solutions either autonomously or with on-demand video assistance greatly improving the limited traditional ATM experience. The 7800 series modular design and high capacity drive Hyosung's industry-leading availability and serviceability. Learn why large and small financial institutions continue to standardize on 7800 series, helping make Hyosung the fastest-growing ATM company in the United States.



# **KEY FEATURES**

#### **INNOVATION**

The **MX7800I** has the ability to deliver transactions through self-service or with the support of on demand video assistance. Our financial institutions' customers prefer self-service first and only video when required approach and do not require a video agent upfront.

#### **HIGHEST AVAILABILITY**

Innovative modular design and the use of Hyosung's manufactured core technologies allow for fast, easy replenishment and reduced downtime. The **MX7800I** is designed to provide reliability that is unequaled in the market, with minimum maintenance and maximum uptime.

#### **USABILITY**

A user interface specifically adapted to accommodate a wide range of drive-thru teller transactions. Multiple customer authentication options include contactless and biometrics.

#### **CAPACITY**

High capacity, cash dispense capability and the ability to support large volume transactions.

#### **FUNCTIONALITY**

The **MX7800I** delivers an unparalleled range of transactions when deployed in conjunction with Hyosung's innovative integrated software approach and powerful video assistance solutions. The **7800 series** comes ready to support a full range of branch transformation transactions, including video.



# **MX7800I**

# **SPECIFICATIONS**

### **DIMENSIONS**

Height: 63.2"Width: 38.6"Depth: 36.6"

Weight: 2,866 lbs.

#### **ENVIRONMENTAL**

 Temperature: 32°F – 104°F (0°C ~ 40°C)

Humidity 25% – 85%

# **SOFTWARE**

- · Microsoft Windows® 7
- · Windows 10 ready

#### **CUSTOMER INTERFACE**

- 21.5" landscape display TFT LCD
- Input Method Touch screen
- Web Camera video camera and microphone (optional)
- PIN Pad PCI compliant
- ADA Audio Guidance earphone iack
- · Card Reader EMV compliant
- Contactless Integrated reader (via card, smartphone or smartwatch)

### **MEDIA TECHNOLOGY**

- Dispense
  - 3,000 notes per cassette
  - Configurable denominations
  - Up to 5 high capacity dispense cassettes
  - Bundle present/retract
  - Note by note rejection- single note reject
  - Automatic shutter
  - Dispense up to 50 notes per transaction

# Cash & Check In Module (CCiM)

- Bundle Capacity: insert mixed bundle of 50 checks and cash per transaction
- 1 cash cassette
- 1 check cassette
- Capacity: Up to 2,000 items per cassette

#### **SECURITY**

- · Safe: UL 291 Level 1
- · Alarm Seismic + Heat
- Locking Device KABA Mas Cencon
- Sensor Safety door sensor
- Security Terminal block for easy security connections
- · Security camera

#### **SERVICING**

- Front access
- State of health indicators across all modules

#### **PRINTER**

3.1" graphical thermal receipt printer

## **ADDITIONAL INFORMATION**

- Communication TCP/IP
- Backup battery reserves the last transaction & safe shutdown

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

Features and benefits are for U.S. configuration only. If located outside of the U.S., please contact sales.

<sup>\*</sup>Subject to note quality and other variables