

The Monimax 5100T is a high-value, through-the-wall ATM that features advanced performance, exceptional reliability, and a wide variety of optional modules. This ATM can easily scale up after installation to suit growing demand.

Features

Powerful Performance

A Windows 7® open platform can handle any application software based on a WOSA/XFS platform. Opt for decreased transaction time, multi-media advertisements, and other advanced services and functions.

Multipurpose

Walk-up, drive-up, through-the-wall, and free-standing kiosk—all are available with the Monimax 5100T. It features a small footprint and compact architecture that offers flexible options at an affordable price.

Small Size, Large Display

An optional 10.4" sunlight-viewable color display is designed to perform clearly—inside or outside.



Superior quality, security and value.

Only with Nautilus Hyosung.

Now offering the most complete line of financial and retail ATMs.



The Monimax 5100T helps you build your ATM revenue with an affordable option that includes easy scalability.

Dependable Customer Service

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

MONIMAX 5100T

System Control

- Intel® Pentium®-IV processor
- Microsoft® Windows 7® platform
- Application NDC+, VISA2

Customer Display

- 10.4" color TFT LCD
- Optional sunlight viewable

Communication

- NDC+ : TCP/IP
- VISA2 : TCP/IP (SSL configurable)
Dial-up

Input Type

- 4 x 2 function keys
- 4 x 4 numeric keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

Card Handling

- Dip-type card reader
- Optional IC card reader, EMV Level 1, 2

Cash Dispensing

- 2,000-note cassette
- Up to four cassettes
- Note-by-note rejection

Printers

- 3.1" graphical thermal receipt printer

Security

- UL291 Business hours
- Standard electronic safe lock
- Voice guidance system
- Optional UL291 Level 1
- Optional KABA Mas Cencon safe lock

Power Supply

- AC 110–230V, 50–60 Hz

Operating Environment

- Temperature: 32°F–104°F
- Optional Tolerance: 14°F–104°F
- Humidity: 25%–86%

Dimension and Weight

- Height: 59.4" (1509.5 mm)
- Width: 23.6" (600 mm)
- Depth: 32.6" (828 mm)
- Weight: 441.5 lbs (200 kg)

Supervisor Operation

- 5.7 Mono Display
- 4x4 Numeric keys
- 4x2 Function keys

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



 NAUTILUS HYOSUNG

Contact your authorized Nautilus Hyosung distributor or representative for more information.